


Low-Surface Energy (LSE) & Low VOC Transfer Tape



Release Liner

Liner:

74# Polycoated Kraft

Adhesive

Adhesive:

Acrylic (I665)

Specifications:

Passes Automotive Fogging Test: SAE J1756 @ 100 °C as tested

Passes Odor Test SAE J1351

Meets numerous other Auto Specs

Applications

- Nameplates
- Attaching to powder coated and other LSE finishes
- Cost effective option for many LSE applications
- Bonding to a variety of high and low surface energy materials such as ABS, powder coated paints, TPO, PE, PET, and more

Features

Benefits

- | | |
|---|---|
| <ul style="list-style-type: none"> • Acrylic Adhesive • 74# Kraft Liner | <ul style="list-style-type: none"> • Quick initial tack • Low fogging, low flammability • High peel and shear properties • Excellent high and low temperature performance • Conformable and good dimensional stability |
|---|---|

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesive Thickness	3.0 mils	0.076 mm	PSTC 133
Liner Thickness	5.5 mils	0.140 mm	PSTC 133
Adhesion to Steel	70.0 oz/in	7.66 N/cm	PSTC 101 Mod - 1 mil PET
Shear Strength	>7 Days		PSTC 107 Mod
Laminating Temperature	68 to 100 °F	20 to 38 °C	
Service Temperature	-30 to 375 °F	-34 to 191 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Berry Global assumes any legal responsibility.